

HAPTIC SENSATIONS FOR TACTILE FEEDBACK INTERFACE DEVICES

5

BY INVENTOR
Louis B. Rosenberg

CROSS REFERENCE TO RELATED APPLICATIONS

10

This application claims the benefit of Provisional Patent Applications no. 60/224,584, filed August 11, 2000 by L. Rosenberg, entitled, "Vibrotactile Interfacing with Graphical Objects," and No. 60/_____, filed September 11, 2000 by L. Rosenberg, entitled, "Vibrotactile Sensations for Displayed Graphical Objects," and both of which are incorporated herein by reference for all purposes.

15

BACKGROUND OF THE INVENTION

20

The present invention relates generally to haptic feedback provided to humans when interfacing with computer systems, and more particularly to haptic sensations and computer interface devices that allow the user to provide input to computer systems and allow computer systems to provide haptic feedback to the user.

25

30

A user can interact with an environment displayed by a computer to perform functions and tasks on the computer, such as playing a game, experiencing a simulation or virtual reality environment, using a computer aided design system, operating a graphical user interface (GUI), etc. Common human-computer interface devices used for such interaction include a mouse, joystick, trackball, steering wheel, stylus, tablet, pressure-sensitive sphere, or the like, that is connected to the computer system controlling the displayed environment. Typically, the computer updates the environment in response to the user's manipulation of a physical manipulandum such as a joystick handle or mouse, and provides visual and audio feedback to the user utilizing the display screen and audio speakers. The computer senses the user's manipulation of the user manipulandum through sensors provided on the interface device that send locative signals to the computer. For example, the computer displays a cursor or other graphical object in a graphical environment, where the location of the cursor is responsive to the motion of the user manipulandum.

In some interface devices, force feedback or tactile feedback is also provided to the user, more generally known herein as "haptic feedback." These types of interface devices can provide physical sensations which are felt by the user manipulating a user manipulandum of the interface device. One or more motors or other actuators are coupled to the joystick, mouse, or other device and are connected to the controlling computer system. In kinesthetic force feedback systems, the computer system controls forces on the movement of the joystick or mouse in conjunction and coordinated with displayed events and interactions by sending control signals or commands to the actuators. For example, the Logitech Wingman Force Feedback Mouse and the Logitech I-Feel Mouse allow a user to experience haptic sensations associated with interacting a cursor with graphical objects in a GUI or web page.

Low-cost haptic devices tend to provide tactile feedback, in which forces are transmitted to a housing or portion thereof and felt by the user, rather than kinesthetic feedback, in which forces are output directly in the degrees of freedom of motion of the interface device. For example, many currently-available gamepad controllers include a spinning motor with an eccentric mass, which outputs vibrations to the housing of the controller in coordination with events occurring in a game. In some haptic mouse devices, pins, buttons, or the housing of the mouse can be vibrated in accordance with interaction of a controlled cursor with other graphical objects, which the user feels by touching those housing areas. These tactile devices are typically less sophisticated than kinesthetic devices and therefore are much less expensive to produce.

One problem with such inexpensive haptic controllers is their limited ability to convey certain types of haptic sensations to the user. For example, most pure tactile mice are incapable of providing spring and damper sensations in the sensed degrees of freedom of the mouse. These types of devices tend to be limited in producing other spatially-based haptic sensations as well. This can limit the applicability of tactile mice to interfaces designed for kinesthetic force feedback devices. For example, many traditional interface elements, such as graphical objects in a graphical user interface, tend to be associated with spatially-based force sensations. Icons, for example, are often associated with attractive and/or repulsive forces, which apply a force on a mouse in its degrees of freedom to assist the user in cursor moving tasks. However, in a tactile mouse providing no such forces in the degrees of freedom of the mouse, such haptic sensations cannot be output. What is needed are haptic sensations to associate with graphical elements in interface tasks that are compelling and useful to a user of a tactile mouse or other tactile interface device.

SUMMARY OF THE INVENTION

The present invention presents different types of tactile sensations which can be used in a variety of applications to convey interesting and useful information to the user of a haptic feedback device.

More particularly, in a first method of the present invention for providing a haptic sensation to a user physically contacting a haptic feedback device, where the haptic feedback device communicates with a host computer implementing a graphical environment, the method includes receiving an indication of an interaction of a user-controlled cursor with a graphical object, and enabling the output of a tactile sensation during the interaction, the tactile sensation being based on a periodic waveform and having a frequency correlated with a size of the graphical object interacted with the cursor. The frequency of the tactile sensation can be correlated with a size of a collection of data associated with the graphical object, or correlated with a displayed size of the graphical object or other size characteristic. The interaction can be moving the cursor over the graphical object or dragging the graphical object. A magnitude or duration of the sensation can also be correlated the size of the graphical object.

In a different aspect of the present invention, a method for providing a haptic sensation to a user physically contacting a haptic feedback device includes receiving an indication of a position of a user-controlled cursor, causing the cursor to snap to the graphical object when the cursor is within a predetermined distance of the graphical object in the graphical environment so that the cursor is displayed touching the graphical object and the cursor can be moved along or within the graphical object based on user manipulation of the haptic feedback device, and enabling the output of a vibration sensation while the cursor is moved along or within the graphical object. The graphical object can be a line and the vibration can be enabled to be output when the cursor moves along the line. Input from the haptic feedback device based on user manipulation that would cause the cursor to move away from the graphical object can be ignored, for example, when the input designates cursor locations within a predetermined distance from the graphical object.

In a different aspect of the present invention, a method for providing a tactile sensation to a user physically contacting a haptic feedback device includes enabling the output of a pop sensation that is a short, high magnitude sensation, and enabling the output of a ringing sensation during or immediately after the output of the pop sensation. The ringing sensation is commanded using a periodic waveform and has a longer duration and lower magnitude than the pop sensation. The ringing sensation can fade in magnitude over time. The haptic sensation can be a

rubbery sensation having a ringing sensation using a periodic waveform having a frequency of 125 to 200 Hz and a duration of about 200 milliseconds, or a metallic sensation having a ringing sensation with a frequency of 300 to 500 Hz and a duration of about 200 milliseconds.

5 The present invention provides a variety of compelling tactile sensations that can be used with a purely tactile feedback interface device. Since tactile devices are typically less complex and expensive to produce than kinesthetic force feedback devices, the tactile sensations presented herein advantageously extend the applicability and desirability of the less expensive tactile feedback devices.

10 These and other advantages of the present invention will become apparent to those skilled in the art upon a reading of the following specification of the invention and a study of the several figures of the drawing.

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205

BRIEF DESCRIPTION OF THE DRAWINGS

FIGURE 1 is a perspective view of an example of a haptic feedback device and host
5 computer suitable for use with the present invention;

FIGURE 2 is a side elevational view of an example implementation of the haptic mouse
device shown in Fig. 1; and

FIGURE 3 is a diagrammatic view of a displayed line object and a cursor interacting with
the object according to one aspect of the present invention.

10
20
30
40
50
60
70
80
90
100
110
120
130
140
150
160
170
180
190
200
210
220
230
240
250
260
270
280
290
300
310
320
330
340
350
360
370
380
390
400
410
420
430
440
450
460
470
480
490
500
510
520
530
540
550
560
570
580
590
600
610
620
630
640
650
660
670
680
690
700
710
720
730
740
750
760
770
780
790
800
810
820
830
840
850
860
870
880
890
900
910
920
930
940
950
960
970
980
990

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

FIGURE 1 is a perspective view of a haptic feedback mouse interface system 10 suitable for use with the present invention and capable of providing input to a host computer based on the user's manipulation of the mouse and capable of providing haptic feedback to the user of the mouse system based on events occurring in a program implemented by the host computer. Mouse system 10 includes a mouse 12 and a host computer 14. It should be noted that the term "mouse" as used herein, indicates an object generally shaped to be grasped or contacted from above and moved within a substantially planar workspace (and additional degrees of freedom if available). Typically, a mouse is a smooth or angular shaped compact unit that snugly fits under a user's hand, fingers, and/or palm, but can also be implemented as a grip, finger cradle, cylinder, sphere, planar object, etc.

Mouse 12 is an object that is preferably grasped or gripped and manipulated by a user. By "grasp," it is meant that users may releasably engage a portion of the object in some fashion, such as by hand, with their fingertips, etc. In the described embodiment, mouse 12 is shaped so that a user's fingers or hand may comfortably grasp the object and move it in the provided degrees of freedom in physical space. For example, a user can move mouse 12 to provide planar two-dimensional input to a computer system to correspondingly move a computer generated graphical object, such as a cursor or other image, in a graphical environment provided by computer 14 or to control a virtual character, vehicle, or other entity in a game or simulation. In addition, mouse 12 preferably includes one or more buttons 16a and 16b to allow the user to provide additional commands to the computer system.

Mouse 12 preferably includes an actuator 18 which is operative to produce forces on the mouse 12. This operation is described in greater detail below with reference to Fig. 2.

Mouse 12 rests on a ground surface 22 such as a tabletop or mousepad. A user grasps the mouse 12 and moves the mouse in a planar workspace on the surface 22 as indicated by arrows 24. Mouse 12 may be moved anywhere on the ground surface 22, picked up and placed in a different location, etc. A sensor system translates the planar motion of the mouse 12 into electrical position signals, which are sent to a host computer 14 over a bus 20 as is well known to those skilled in the art. Mouse 12 is preferably a "relative" device, which, as referenced herein, is a device that reports a change in position of the device to the host computer rather than an absolute position in a fixed reference frame.

Mouse 12 is coupled to the computer 14 by a bus 20, which communicates signals between mouse 12 and computer 14 and may also, in some preferred embodiments, provide

power to the mouse 12. Components such as actuator 18 require power that can be supplied from an interface such as a USB or Firewire (IEEE 1394) bus. In other embodiments, signals can be sent between mouse 12 and computer 14 by wireless transmission/reception. In some embodiments, the power for the actuator can be supplemented or solely supplied by a power storage device provided on the mouse, such as a capacitor or one or more batteries.

Host computer 14 is a computing device that can take a wide variety of forms. For example, computer 14 can be a personal computer or workstation, such as a PC compatible computer or Macintosh personal computer, or a Sun or Silicon Graphics workstation. For example, the computer 14 can operate under the Windows™, MacOS, Unix, or MS-DOS operating system. Alternatively, host computer system 14 can be one of a variety of home video game console systems commonly connected to a television set or other display, such as systems available from Nintendo, Sega, Sony, or Microsoft. In other embodiments, host computer system 14 can be a “set top box” which can be used, for example, to provide interactive television functions to users, or a “network-” or “internet-computer” which allows users to interact with a local or global network using standard connections and protocols such as used for the Internet and World Wide Web. Computer 14 can also be a portable computer or game device, arcade machine, vehicle computer, etc. Host computer preferably includes a host microprocessor, random access memory (RAM), read only memory (ROM), input/output (I/O) circuitry, disk drives, and other components of computers well-known to those skilled in the art.

Host computer 14 preferably implements a host application program with which a user is interacting via mouse 12 and other peripherals, if appropriate, and which may include force feedback functionality. For example, the host application program can be a drawing/CAD program, video game, word processor or spreadsheet, Web page or browser that implements HTML or VRML instructions, scientific analysis program, virtual reality training program or application, or other application program that utilizes input of mouse 12 and outputs force feedback commands to the mouse 12. Herein, for simplicity, operating systems such as Windows™, MS-DOS, MacOS, Linux, Be, etc. are also referred to as “application programs.” In one preferred embodiment, an application program utilizes a graphical user interface (GUI) to present options to a user and receive input from the user. Herein, computer 14 may be referred as providing a “graphical environment,” which can be a graphical user interface, game, simulation, or other visual environment. The computer displays “graphical objects” or “computer objects,” which are not physical objects, but are logical software unit collections of data and/or procedures that may be displayed as images by computer 14 on display screen 26, as is well known to those skilled in the art. The host application program checks for input signals derived from the electronics and sensors of mouse 12, and outputs force values and/or commands to be converted

into forces output for mouse 12. Suitable software drivers which interface software with haptic feedback devices are available from Immersion Corporation of San Jose, California.

Display device 26 can be included in host computer 14 and can be a standard display screen (LCD, CRT, flat panel, etc.), 3-D goggles, or any other visual output device. Typically, the host application provides images to be displayed on display device 26 and/or other feedback, such as auditory signals. For example, display screen 26 can display graphical objects from a GUI and/or application program.

Mouse 12 can include a wide variety of architectures. For example, in some embodiments, the host computer 14 controls the output of actuators on the mouse 12 directly by streaming force values to the mouse 12. In other embodiments, a local microprocessor on the mouse 12 can receive high level commands from the host 14 and provide the force values to the actuator based on the host commands and local force processes. These implementations, and variations thereof, are described in copending application no. 09/456,887, filed 12/7/99, incorporated herein by reference.

In alternative embodiments, the mouse can be a different interface or control device. For example, a haptic feedback trackball, a hand-held remote control device, gamepad controller for video games or computer games, a knob, cellular phone, personal digital assistant, touchpad, stylus, joystick, steering wheel, etc. can be used with the present invention.

FIGURE 2 is a side cross-sectional view of one embodiment 40 of mouse 12 of Fig. 1. Mouse 12 includes one or more actuators 18 for imparting haptic feedback such as tactile sensations to the user of the mouse. Suitable embodiments and mechanisms for use as a tactile mouse or other tactile pointing device (trackball, gamepad, joystick, stylus, etc.) are well known to those of skill in the art. For example, suitable embodiments for a tactile mouse are described in Patent No. 6,211,861 and copending application nos. 09/585,741 and 09/759,780, all incorporated herein by reference.

Mouse 12 includes a housing 50, a sensing system 52, and an actuator 18. Housing 50 is shaped to fit the user's hand like a standard mouse while the user moves the mouse in the planar degrees of freedom and manipulates the buttons 16. Other housing shapes can be provided in many different embodiments. Buttons 16 can be selected by the user as a "command gesture" when the user wishes to input a command signal to the host computer 14.

Sensing system 52 detects the position of the mouse in its planar degrees of freedom, e.g. along the X and Y axes. In the described embodiment, sensing system 52 includes a standard mouse ball 54 for providing directional input to the computer system. Ball 45 is a sphere that

extends partially out the bottom surface of the mouse and rolls in a direction corresponding to the motion of the mouse on a planar surface 22. For example, when the mouse 12 is moved in a direction indicated by arrow 56 (y direction), the ball rotates in place in a direction shown by arrow 58. The ball motion can be tracked by a cylindrical roller 60 which is coupled to a sensor 62 for detecting the motion of the mouse. Sensor 62 be any of a variety of types of sensors, such as optical encoders, analog potentiometers, etc. A similar roller and sensor 28 can be used for the x-direction which is perpendicular to the y-axis. Other types of mechanisms and/or electronics for detecting planar motion of the mouse 12 can be used in other embodiments. For example, an optical sensor can be used to track mouse motion; a suitable optical mouse technology is made by Hewlett Packard of Palo Alto, CA and is used in, for example, the Intellimouse® Explorer or Intellimouse® with Intellieye™ mouse devices from Microsoft Corporation. Use of this sensor is described in greater detail in U.S. Patent No. 6,211,861. Alternatively, a portion of an optical sensor can be built into the surface 22 (such as a pad) to detect the position of an emitter or transmitter in mouse 12 and thus detect the position of the mouse 12 on the surface 22.

An actuator 18 is coupled to the housing 50 to provide haptic feedback to the user. In one embodiment of the present invention, an actuator is coupled to an inertial mass that is moved by the actuator. The actuator is also coupled to the housing of the mouse such that inertial forces caused by the motion of the inertial mass with respect to an inertial ground are applied to the housing of the mouse, thereby conveying haptic feedback such as tactile sensations to the user of the mouse who is contacting the housing. Sensations can alternative or additionally be output with reference to an earth ground, e.g. by moving a portion of the housing against the user, as described in copending application 09/585,741. One embodiment 40 creates inertial forces that are directed substantially in a particular degree of freedom, i.e. along a particular axis. The inertial forces can be created, for example, using a high bandwidth linear actuator, such as a linear moving voice coil actuator and a linear moving-magnet actuator. A flexure or other mechanism can be used to convert rotary forces to substantially linear forces in a desired direction, such as along the Z-axis, orthogonal to the planar X and Y axes used for mouse motion and input.

In the described embodiment, actuator 18 can be a linear electromagnetic actuator having a stationary portion 66 coupled to the mouse housing 50 (and thus stationary only with respect to the portion of the mouse housing to which it is coupled), and a moving portion 67 that moves linearly approximately along the Z-axis. In the described embodiment, the stationary portion 66 includes a magnet and the moving portion 67 includes a wire coil. An inertial mass 64 is coupled to (or is integral to) the linearly-moving portion of the actuator. The actuator 18 is operative to oscillate the inertial mass 64 quickly along the axis C which is approximately parallel to the Z

axis. Thus, inertial forces produced by the moving mass 64 are transmitted to the housing through the stationary portion 66 of the actuator 18 and felt by the user. These forces are substantially directed along the Z axis. Preferably, the mass has an origin position that is positioned between the extremes of the range of motion of the mass. In some embodiments, a spring compliance is built into the actuator or the mass so that the mass returns to the origin position when no forces are exerted on the mass by the actuator.

In other embodiments, moving surface tactile sensations can be conveyed to the user instead of inertial sensations. For example, a surface on the mouse, on a housing, a touchpad, or other contacted surface can be directly moved in the z-axis against the user's finger or palm. Or, the contacted surface can oscillated side-to-side in the x-y plane, conveying tactile sensations in shear on the user's skin. These types of tactile sensations can also be used with the present invention.

Actuator 18 can be a linear voice coil actuator as described in Patent No. 6,243,078, which is incorporated herein by reference in its entirety. Alternatively, actuator 18 can be other types of actuators/mechanisms, such as a DC motor and flexure. A variety of tactile sensations can be output to the user, many of which are described in Patent No. 6,211,861. A block diagram of a haptic feedback system, including local control such a microprocessor or host control, and which can be suitable for the present invention is described in Patent Nos. 6,211,861, 6,243,078, and 5,825,308, all incorporated herein by reference in their entirety.

In addition, it is preferred that the mouse rest on a flexible or semi-flexible surface, such as a standard mouse pad. This type of flexible surface increases the transmissibility of the inertial forces from the actuator to the housing and allows the inertial sensations to be amplified, rather than countered by normal forces applied by a hard surface such as a table surface. An amount of flex can also be provided between the actuator-coupled portion of the mouse housing and the base portion 68 that is in contact with the surface 22 to improve the transmissibility of the tactile sensations.

Tactile Sensations

Tactile sensations applied to the user operating a tactile feedback interface device can take a variety of forms. Tactile sensations of the present invention which have been found to be particularly suitable for interface tasks, such as tasks within a graphical user interface or application program, are described below.

Any of the tactile sensations described below can be controlled by a driver program running on the host computer, by an application program or API on the host computer, or by the local microprocessor on the haptic feedback device, or by a combination of two or more of these. For example, a driver program on the host (at a lower level than the application program) can check when a cursor interacts with an object and cause the necessary commands to be output to implement a tactile sensation to the haptic device. Or, an application program on the host can command the haptic sensations directly. Alternatively, a local microprocessor or other controller can check cursor interactions and command sensations, as long as the local microprocessor has an up-to-date picture of the layout of the graphical environment, e.g. the host can send data to the microprocessor conveying this information.

Conveying a Sense of Object Size

In kinesthetic force feedback devices of the prior art, forces can be output in the degrees of freedom of the mouse. Thus, for example, a displayed icon can be associated with an attractive force, where forces are output in the direction of the icon to draw the mouse toward the icon.

In other situations, a sense of the size of a graphical object (or an associated collection of data) can be conveyed when the user uses the mouse to move the graphical object or move the cursor over the object. For example, in Patent No. 6,219,032, incorporated herein by reference in its entirety, a user can move a cursor on some types of graphical objects and “drag” them, e.g. move the objects with the cursor while holding down a mouse button. In kinesthetic feedback devices, to make the objects feel as if they have weight, a force can be output in conjunction with the drag operation, such as an inertia force or resistance force in the opposite direction to the drag direction. To convey a size of the object, the magnitude of the force can be in proportion to the size of the object. Thus, a smaller graphical object will provide a smaller resistance force, while a larger graphical object provides a larger resistance force. The force magnitude can also or alternatively be indicative of a collection of data, program, or other quantity or feature associated with the graphical object. For example, the force for a folder can be proportional to the number of files stored within that folder, and/or proportional to the size (e.g. in bytes) of a file within that folder. In other kinesthetic force feedback embodiments, an attractive force can bias the device or manipulandum to move the cursor toward an object, and the attractive force magnitude can be scaled in proportion with the size of object or size of an associated characteristic.

Purely tactile mice, however, such as the embodiment described with reference to Fig. 2, cannot output forces in the degrees of freedom of the mouse and thus cannot output drag forces,

inertia forces, attractive forces, or the like. However, haptic sensations can be output to convey to the user a size of graphical object which is being manipulated or moved over with the cursor.

Tactile sensations can be conveyed by commanding a periodic waveform to the actuator. For example, a sine wave that moves positive and negative can cause the actuator to move an inertial mass in positive and negative directions about an origin position, thereby conveying a vibration sensation. A square wave, triangle wave, sawtoothed-shaped wave, or other types of periodic waveforms can also be commanded. Many different types of vibration sensations and other sensations can be designed and output using such software tools and programs as Immersion Studio™ and Immersion Desktop™, available from Immersion Corp.

The duration, or number of periods in the commanded wave, determines how long the vibration sensation is output. If a small number of high frequency periods of a waveform are commanded, it typically feels like a single “pulse” or jolt of force to the user, since the oscillatory motion occurs too quickly for the user to notice.

Such pulses can be associated with graphical objects in a graphical user interface, application program, or other displayed graphical environment. For example, when the user interacts the cursor with a graphical object, a short duration periodic waveform is preferably sent to the mouse, causing a short vibration or “pulse” to be experienced by the user. This pulse can be output when the cursor enters a graphical object or exits the object, or when the cursor moves over the middle of the object (e.g., for smaller graphical objects). Graphical objects associated with such forces can include menu items, icons, buttons, tool bars, slider thumbs, radio buttons, check boxes, and hyperlinks or other objects in a web page. Web page force sensations are described in U.S. Patent No. 5,956,484, incorporated herein by reference in its entirety.

According to the present invention, a size of the graphical object can also be conveyed using tactile sensations. The frequency and duration of the waveform can be adjusted to convey this size. For example, when the user moves the cursor over a small menu item, a tactile sensation is output by commanding a high frequency vibration to the device which preferably has a short enough duration to convey a small number of cycles (or periods) of the vibration, such as two to five. For example, a waveform having a frequency of 125 Hz and a duration of 14 milliseconds can convey this sensation. To the user, this feels like a small jolt or pulse on the mouse which indicates the graphical object has been engaged or interacted with the cursor. As another example, the sensation of an even smaller object, such as a radio button, can be conveyed by commanding a periodic waveform having a very high frequency and a very short duration, such as 300 Hz for 5 milliseconds. These vibrations are a high enough frequency as to feel like a single jolt or pulse to the user. A low magnitude for the vibration can also be specified to enhance the “small” perception to the user, but magnitude typically is not as important as

frequency, since the user is typically able to adjust the magnitude (gain) of all forces output on the mouse device. Distinguishing a small object by frequency is independent of any such gain control and thus more reliable.

When the user moves the cursor over a larger graphical object, such as a large toolbar icon or a desktop icon, a waveform having a lower frequency is preferably commanded. To convey the preferable 2-5 cycles of vibration, the waveform will typically also have a longer duration than the higher frequency waveforms for smaller graphical objects. A waveform having, for example, a frequency of 83 Hz and a duration of 25 milliseconds can be used. This provides the sensation to the user of moving the cursor over or into a large bump or other obstruction, i.e. the lower frequency and longer duration pulse conveys the feeling of a larger object.

The pulses or vibrations for different sizes of objects can be varied to a fine degree. For example, the frequency and duration of the vibrations can be adjusted in 10 Hz and 10 millisecond increments according to the size of the associated graphical object, or a more gradual adjustment can be used. When experiencing the different feels of all of the graphical objects, the user correlates the different force sensations with differently-sized objects so that the user intuitively knows the sizes of graphical objects simply by the tactile sensations associated with those objects.

In other embodiments, the frequency and duration of a commanded waveform can convey the size of associated data, application program, or other characteristic. For example, a displayed graphical icon can be associated with a file having a size in bytes. A high frequency waveform, as described above, can be commanded to output a vibration for smaller file sizes associated with icons, while lower frequency waveforms can be used to command pulses for larger file sizes. Similarly, the size or importance of an associated application program can be similarly conveyed via frequency and duration. The different pulses can also be made to convey the importance of a graphical object with regard to the preferences of a particular user.

Tactile Drawing Application Sensations

Drawing, graphics, and computer-aided design (CAD) application programs allow a user to input and edit line drawings, bitmaps, and other pictorial works displayed on the computer display device. In many types of line drawing applications, a user can move a cursor over a line, shape, or other drawing object and select the object with the cursor. The user can then

manipulate or edit the object in several ways, such as move or delete the object, change the shape or facing of the object, resize the object, change the color of the object, etc.

Existing kinesthetic force feedback mouse implementations output forces in the planar degrees of freedom of the mouse and thus can provide forces that directly assist the user in selecting a desired drawing object and tracing over that object. For example, a line object can be associated with attractive forces so that when the cursor is moved within a predetermined distance of the line object, the attractive force is activated, causing the mouse to be biased in a direction toward the line object. When the cursor is positioned on or very near the line object, the attractive forces act to resist movements of the cursor away from the line object. This provides a "snap to" sensation that allows the user to select the line object more easily. In addition, the user can directly feel the shape of the line by moving the cursor along the line object. If the user moves the mouse away from the line, the forces bias the mouse back toward the line so that the user can more easily trace the line with the cursor.

In purely tactile haptic devices, no such attractive or snap-to forces can be output in the degrees of freedom of the mouse or other manipulandum. However, according to the present invention, forces can be output to inform and assist the user in selecting and tracing drawing objects or the like. In one preferred embodiment, when the cursor is moved within a predetermined distance of an object such as a line, the cursor is visually caused to snap to the line, i.e., the host computer displays the cursor at the line, which may cause the cursor to move on the screen without any user motion of the mouse. An example is shown in FIGURE 3, which shows a line 100 displayed on a display screen. If the cursor moves within a specified distance of the line 100, indicated by dashed line 102 (preferably not displayed, but can be displayed in alternate embodiments), the cursor 104 is displayed at the line 100 as shown. The distance can vary in different embodiments, and even be specifiable by the user as one or more preferences in an application program.

In one embodiment, once the cursor is positioned on the line, the user may move the mouse to move the cursor along the line. If mouse motions cause the cursor to move along the line, then the display of the cursor is not modified. If, however, the mouse is moved in a direction that would cause the cursor to move away from the line, then the mouse input in that direction is ignored. This causes the cursor to remain on the line regardless of mouse input. For example, if the cursor is on a line that is horizontal, then mouse motion in a diagonal direction (horizontal plus vertical components) would cause the cursor to move along the horizontal line, but not in any vertical direction. Preferably, only mouse motion within a predetermined radius of the snap-to object is filtered in such a way; this radius can be the same as the entering distance (indicated by line 102), or can be made a different distance. In alternate embodiments, the cursor

can be allowed to move within the area defined by line 102 before the mouse inputs are filtered or ignored (e.g. the non-line mouse motions can be ignored out to a distance from the line 100 greater than line 102).

According to the present invention, while the cursor is snapped to the line, a vibration sensation is preferably output while the cursor is engaged with the line (e.g., while the cursor is positioned to select the line). The vibration is preferably a high frequency vibration that indicates to the user that the cursor is engaged with or positioned over or near the line. The vibration can also have a lower magnitude. To the user, the line then feels as if it were a "live wire," e.g., as if he or she were touching a wire having electricity flowing through it, or as if touching a cord having sound vibrating through it. This indicates to the user that the line may be selected, but is not so strong a force sensation as to cause a disturbance to the user or impede the cursor motion. Furthermore, it is a very compelling sensation to move the cursor along the line and feel the vibration. When the cursor moves off the line, the user is immediately aware that selection is no longer possible.

In other embodiments, a different vibration can be commanded. For example, one or more of the vibration characteristics can be made proportional to the current velocity of the mouse in its workspace. In one embodiment, low mouse velocities cause a vibration having a lower magnitude and/or frequency, while higher mouse velocities cause a vibration having a higher magnitude and/or frequency.

It should be noted that other types of graphical object which are traced by the cursor can be correlated with vibrations as described above. For example, the outlines of polygons or other shapes can be implemented similarly to the line object described above. Furthermore, background lines or shapes, such as grid lines, may be associated with such haptic sensations in some applications.

Rubbery and Metallic Interactions

In many force feedback interfaces to graphical environments, it is desirable to create unique and individual haptic sensations that can indicate needed information to the user concerning an interaction of the controlled cursor with another displayed object, or concerning some other event.

One type of haptic sensation that can be both compelling and informative to the user is a "rubbery" or "metallic" sensation. To the user, these types of sensations feel like tapping a finger or a held object on a rubber-like ringing material, or a metallic ringing material, where an amount

of ringing or vibration occurs after a tap. Displayed objects such as icons, menus, toolbars, hyperlinks, or checkboxes can be provided with such a feel. For example, a user may prefer a rubbery sensation when moving a cursor between menu items or when moving the cursor onto an icon.

5 In addition, certain types of objects can be associated with this type of haptic sensation to distinguish those types of objects from other types of objects. The rubbery and metallic feels can also be used to distinguish some interface functions from other functions, e.g. distinguishing the selection of a button from the selection of a drop down menu in an interface. Events, such as the reception of email or a calendar reminder, can also be distinguished with the rubbery or metallic
10 feels. In some embodiments, a user can designate his or her own types of objects or instances of objects with the sensations or variations thereof. Some applications such as games or simulations can use the rubbery or metallic feels to provide particular effects when the user is interacting with objects in a graphical environment, such as when a controlled character encounters a surface or other object. Alternatively, game events can be distinguished by the
15 rubbery or metallic sensations, such as when a player is being attacked by another player. One type of event or interaction can be provided with a rubbery feel, while another type can be provided with a metallic feel or a more standard vibration or pulse.

20 An effective way of providing such a rubbery or metallic feel to a displayed object for a tactile interface device is to combine a "pop" sensation with a reverberating "ring" sensation. The pop sensation is a short jolt or "pulse" of force which preferably has a high amplitude relative to the ringing sensation. The pop sensation can be implemented in many different ways. For example, a basic implementation is to move an inertial mass with a high amplitude, e.g. a high amplitude amount of current is sent to a motor for a short period of time. In other implementations, the pop can be provided by commanding one or a small number of periods of a
25 high magnitude vibration. If a small number of high frequency periods of a waveform are commanded, it typically feels like a single "pulse" or jolt of force to the user, since the oscillatory motion occurs too quickly for the user to notice. The pop sensation is preferably output first when the cursor first interacts with the target, to signify to the user the engagement of the cursor with the target, or is output at the beginning of the event notification associated with the rubbery
30 or metallic sensation.

A ring sensation follows the pop and provides the rubbery or metallic ringing characteristic of the sensation, e.g. while the cursor is interacting with an associated target or during an associated event. The ring is a long vibration that is of a lower magnitude than the pop to provide a more subtle effect to the user. In preferred embodiments, the ring sensation fades in

magnitude over time. To achieve a metallic feel, a higher frequency vibration is preferably used for the ring sensation. To achieve a rubbery feel, a lower frequency vibration is preferably used.

Some examples of the described sensations are provided below. For a rubbery sensation associated with a graphical object (or associated with some other event), the following haptic sensations can be characterized:

--pop: a short, high magnitude pulse or vibration

--ring: a periodic waveform having a duration of 200 milliseconds. The frequency of the waveform is preferably in the range of 125 Hz to 200 Hz. The waveform can be, for example, a square wave, sine wave, triangle wave, or other type of wave. The initial magnitude is preferably about 40% of the magnitude of the initial pop sensation. The magnitude preferably fades over the 200 millisecond period, the ending magnitude being less than 20% of the magnitude of the initial pop.

To provide a metallic haptic sensation associated with a graphical object (or another event), the following characteristics can be defined:

--pop: a short, high magnitude pulse or vibration

--ring: a periodic waveform having a duration of about 200 milliseconds. The frequency of the waveform is preferably in the range of 300 Hz to 500 Hz. Square, sine, triangle, or other types of waves can be used. The initial magnitude is preferably about 10-20% of the magnitude of the initial pop sensation. The magnitude preferably fades over the 200 millisecond period, the ending magnitude being nearly zero.

In some embodiments, the ring sensation can start immediately after the pop sensation has been output. In other embodiments, the ring sensation can start at the same time as the pop sensation, or soon after but before the pop sensation is finished. Since the pop sensation has a very short duration, a user cannot distinguish the difference in the ring sensation start times. The most important characteristic is that a high magnitude, fast jolt is followed by the softer, fading reverberation sensation.

The sensations described above can be designed and output using such software tools and programs as Immersion Studio™ and Immersion Desktop™, available from Immersion Corp.

While this invention has been described in terms of several preferred embodiments, it is contemplated that alterations, permutations and equivalents thereof will become apparent to

those skilled in the art upon a reading of the specification and study of the drawings. For example, many different embodiments of haptic feedback devices can be used to output the tactile sensations described herein, including joysticks, steering wheels, gamepads, and remote controls. Furthermore, certain terminology has been used for the purposes of descriptive clarity, and not to limit the present invention. It is therefore intended that the following appended claims include alterations, permutations, and equivalents as fall within the true spirit and scope of the present invention.

5

10
15
20
25
30
35
40
45
50
55
60
65
70
75
80
85
90
95
100